

MODEL V75

VERTICAL SHAFT IMPACT CRUSHER SPECIFICATIONS

- Heavy duty utilized mainframe construction, with adjustable slide base motor mounts. And, removable end screens and belly pans.
- 1/2" thick removable lid with high chrome segmented lid liners.
- Cast high chrome drive tunnel and pedestal liners.
- Rolled one-piece Tub liner.
- Adjustable cast 8" Diameter Feed tube and 24" Diameter Feed hopper.
- Removable bearing pedestal with high alloy shaft and spherical roller bearings.
- Hydraulic oil lube system with spin on filter, fluid level / temperature gauge and low pressure shut down switch.
- 18" Diameter impeller table with 3,4, or 5 shoes.
- Removable anvil ring with segmented anvils.
- Complete unit primered and painted with machinery enamel.
- Two-year factory warrantee.
- Maximum horsepower required 150.
- Minimum Horsepower required 50.
- Maximum feed size depending on RPM 1.5"
- Maximum RPM depending on feed size 2600.
- Maximum though put tonnage depending on feed size and installed horse power 75.
- Optional hydraulic lid lifter and hydraulic adjustable feed tube

NOTE:

VSI Crushers are very application sensitive machines. There are various internal configurations and wear parts designs available. Feed size, product specifications, through put tonnage, material type, hardness, abrasiveness and required horse power can all be determining factors when choosing internal components. *We recommend that each application be reviewed by the factory prior to order placement.*